



01000B Motor Oil 20W-50 Multi Grade Classic

Document version: May 20, 2024



Description

This mineral motor oil has been specially developed for engines of classic cars constructed before 1980.

According to the specifications of

API CD / SF / SG
CCMC D1
CCMC G2
Ford M2C9011-A
GM 6085M
MIL-L-46152B

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
01001B	1 L	6	450
01004B	4 L	4	112
01005B	5 L	4	112
01020B	20 L	1	30
01060B	60 L	1	6
01205B	205 L	1	2
01999B	1000 L	1	-
P01000B	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.880	kg/l	ASTM D4052
Viscosity	20W-50		SAE
Kinematic Viscosity at 40°C	166	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	18.1	mm ² /s	ASTM D445
Viscosity Index	121		ASTM D2270
Dynamic Viscosity at -15°C	8500	mPa.s	ASTM D5293
Flashpoint COC	235	°C	ASTM D92
Pourpoint	-24	°C	ASTM D6892
Total Base Number	5.5	mgKOH/g	ASTM D2896
Sulphated Ash	0.6	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.