



05000E Motor Oil 5W-30 Premium Synthetic Fuel Conserving Ford

Document version: May 20, 2024



Description

This premium synthetic fuel-saving motor oil with Ford M2C913-C/D specification has been specially developed for all Ford passenger cars and light commercial vehicles. This motor oil offers optimum protection for diesel, petrol and LPG engines. This motor oil is also suitable for vehicles where SAE 5W-30 with the ACEA A5/B5 specification is required.

According to the specifications of

ACEA A5/B5
API CF / SN
Ford WSS-M2C913-C / WSS-M2C913-D
Jaguar/Land Rover STJLR.03.5003

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001E	1 L	6	450
05004E	4 L	4	112
05005E	5 L	4	112
05020E	20 L	1	-
05B20E	20 L	1	-
05060E	60 L	1	-
05205E	205 L	1	-
05999E	1000 L	1	-
P05000E	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.852	kg/l
Viscosity	5W-30	
Kinematic Viscosity at 40°C	53.3	mm ² /s
Kinematic Viscosity at 100°C	9.66	mm ² /s
Viscosity Index	168	
Flashpoint COC	220	°C
Pourpoint	-45	°C
Total Base Number	10.1	mgKOH/g
Sulphated Ash	1.09	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.