



# 16000ZF6S ATF Automatic Transmission Fluid ZF6/8/9 Special

Document version: May 20, 2024



## Description

This premium synthetic ATF ZF6 Special automatic transmission oil has been specially developed for use in selected 6/8/9-speed automatic transmissions.

## According to the specifications of

BMW 83 22 2 152 426  
Chrysler 68157995A  
Fiat 9.55550-AV5  
Jaguar 02JDE26444  
Land Rover LR023288  
Rolls-Royce 83 22 2 152 426  
VW G 060 162

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001ZF6S	1 L	6	450
16004ZF6S	4 L	4	112
16020ZF6S	20 L	1	30
16060ZF6S	60 L	1	6
16205ZF6S	205 L	1	2
16999ZF6S	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.848	kg/l	ASTM D4052
Colour	green		Visual
Viscosity 10W			
Kinematic Viscosity at 40°C	28.1	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	5.94	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	164		ASTM D2270
Dynamic Viscosity at -40°C	9500	mPa.s	ASTM D5293
Flashpoint COC	210	°C	ASTM D92
Pourpoint	-48	°C	ASTM D97

These characteristics are typical of current production. Variations in these characteristics may occur.