



# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878  
Issue date: 19-8-2011 Revision date: 28-5-2021 Supersedes: 15-1-2015 version: 2.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic  
Product code : 52000S  
Type of product : Other engine, gear and lubricating oils.  
Product group : Blend

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Use of the substance/mixture : Automotive care products  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

MPM International Oil Company  
Cyclotronweg 1  
2629 HN Delft Delft - Nederland  
T +31 (0)15 2514030 - F +31 (0)15 2514031  
[msds@mpmoil.nl](mailto:msds@mpmoil.nl) - [www.mpmoil.nl](http://www.mpmoil.nl)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Comments : Highly refined mineral oil, contains <3% (w/w) DMSO extract, according to IP346

# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction products of benzeneamine, N-phenyl- with nonene (branched)	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	≥ 1 – ≤ 2,49	Aquatic Chronic 4, H413
Phosphorodithioic acid, mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts	(CAS-No.) 84605-29-8 (EC-No.) 283-392-8 (REACH-no) 01-2119493626-26	≥ 1 – ≤ 2,49	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Base oil - unspecified	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	≥ 1 – ≤ 1,49	Asp. Tox. 1, H304

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Phosphorodithioic acid, mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts	(CAS-No.) 84605-29-8 (EC-No.) 283-392-8 (REACH-no) 01-2119493626-26	( 6,25 ≤ C < 100) Skin Irrit. 2, H315 ( 10 ≤ C < 12,5) Eye Irrit. 2, H319 ( 12,5 ≤ C < 100) Eye Dam. 1, H318

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

After inhalation	: Not required.
After skin contact	: Wash skin with mild soap and water.
After eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes.
After ingestion	: Do NOT induce vomiting. Rinse mouth out with water. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

After inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
After skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
After eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
After ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray, powder, foam and CO <sub>2</sub> .
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

#### 6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Detergent. Clean up any spills as soon as possible, using an absorbent material to collect it.
Other information	: Spill area may be slippery. Use suitable disposal containers.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Handling temperature	: < 40 °C
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Store in a closed container.
Storage temperature	: ≤ 40 °C
Storage area	: Store in dry, well-ventilated area.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Additional information	: Based on ACGIH TLV, a concentration of 5 mg/m <sup>3</sup> oilspray (TWA, 8 hour workday) is recommended.
------------------------	---

### 8.2. Exposure controls

#### Personal protective equipment:

Safety glasses. Gloves.

#### Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,35		EN ISO 374

#### Eye protection:

Safety goggles

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily liquid.
Colour	: Amber.
Odour	: Characteristic.
Odour threshold	: No data available

# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C @ ASTM D92
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 852 kg/m <sup>3</sup> @ 15°C
Solubility	: Slightly soluble, the product remains on the water surface.
Log Pow	: No data available
Viscosity, kinematic	: 116 mm <sup>2</sup> /s @ 40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 0 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal conditions.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No naked flames, sparks, and do not smoke.

### 10.5. Incompatible materials

Strong oxidizing agent. Acids and bases.

### 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Base oil - unspecified (64742-54-7)

LD50 oral	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h

#### Phosphorodithioic acid, mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)

LD50 oral rat	3150 mg/kg OECD 401
LD50 dermal rat	> 2002 mg/kg OECD 402
LC50 Inhalation - Rat	> 2,3 mg/l/4h OECD 403

#### Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

LD50 oral rat	> 5000 mg/m <sup>3</sup> (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)
Skin corrosion/irritation	: Not classified

# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

### Base oil - unspecified (64742-54-7)

NOAEL (dermal, rat/rabbit)	> 2000 mg/kg bodyweight
----------------------------	-------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

### Base oil - unspecified (64742-54-7)

NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight/day
NOAEL (subacute, oral, animal/male, 28 days)	> 220 mg/kg bodyweight
NOAEL (subchronic, oral, animal/male, 90 days)	> 980 mg/kg bodyweight

Aspiration hazard	: Not classified
-------------------	------------------

### 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

Viscosity, kinematic	116 mm <sup>2</sup> /s @ 40°C
----------------------	-------------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

### Base oil - unspecified (64742-54-7)

LC50 fish 1	> 100 mg/l
-------------	------------

### Phosphorodithioic acid, mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)

LC50 fish 1	4,5 mg/l <i>Oncorhynchus mykiss</i>
LC50 fish 2	46 mg/l <i>Cyprinodon variegatus</i>
LC50 other aquatic organisms 1	10000 mg/l @0,1d - Chlorophyta
EC50 Daphnia 1	23 mg/l OECD 202
EC50 Daphnia 2	0,8 mg/l @21d
EC50 other aquatic organisms 2	10000 mg/l @0.1d - Chlorophyta
EC50 72h - Algae [1]	21 mg/l @3d - Chlorophyta
ErC50 (algae)	21 mg/l 72h <i>Desmodesmus subspicatus</i> OECD 201
NOEC (acute)	1,8 mg/l @4d - <i>Oncorhynchus mykiss</i>
NOEC (chronic)	> 10 mg/l @2d - Daphnia
NOEC chronic fish	0,4 mg/l @21d - Daphnia
NOEC chronic algae	10 mg/l @3d - Chlorophyta
NOEC (acute)	1.8 mg/l OECD 203 ( <i>Oncorhynchus mykiss</i> )

### Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

LC50 fish 1	100 mg/l OECD 203 ( <i>Danio rerio</i> @96h)
EC50 Daphnia 1	> 100 mg/l OECD 202 ( <i>Daphnia magna</i> @48h)
EC50 other aquatic organisms 1	> 100 mg/l OECD 201 ( <i>Desmodesmus subspicatus</i> @72h)

# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.2. Persistence and degradability

#### 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

#### Phosphorodithioic acid, mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)

Biodegradation	1,5 % @28d OECD TG 301 B
----------------	--------------------------

#### Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

Biodegradation	1 % @28d
----------------	----------

### 12.3. Bioaccumulative potential

#### Phosphorodithioic acid, mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)

Log Kow	0,56 Measurements
---------	-------------------

#### Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

Log Pow	> 7,6
---------	-------

Bioaccumulative potential	Bioaccumulative potential.
---------------------------	----------------------------

### 12.4. Mobility in soil

#### Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

Soil	Adsorbs into the soil.
------	------------------------

### 12.5. Results of PBT and vPvB assessment

#### Component

Phosphorodithioic acid, mixed 0,0-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts (84605-29-8)	The product does not meet the PBT and vPvB classification criteria
--	--

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

No additional information available

## SECTION 14: Transport information

In accordance with ADR / IMDG

ADR	IMDG
<b>14.1. UN number</b>	
Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>	
Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>	
Not applicable	Not applicable
<b>14.4. Packing group</b>	
Not applicable	Not applicable
<b>14.5. Environmental hazards</b>	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

### 14.6. Special precautions for user

#### Overland transport

No data available

#### Transport by sea

No data available

# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

### Indication of changes:

Section	Changed item	Change	Comments
	Supersedes	Added	
	Revision date	Modified	
1.1	Product form	Added	
2.2	EUH-statements	Modified	
3	Composition/information on ingredients	Modified	
4.1	After skin contact	Modified	
4.1	After ingestion	Modified	
4.1	After eye contact	Modified	
4.2	After skin contact	Modified	
4.2	After inhalation	Modified	
4.2	After ingestion	Modified	
4.2	After eye contact	Modified	
5.1	Unsuitable extinguishing media	Added	
5.1	Suitable extinguishing media	Added	
5.3	Precautionary measures fire	Added	
5.3	Protection during firefighting	Added	
5.3	Firefighting instructions	Added	
6.1	Protective equipment	Added	
6.1	Protective equipment	Added	
6.2	Environmental precautions	Modified	
6.3	For containment	Added	
6.3	Methods for cleaning up	Added	
6.3	Other information	Added	
7.1	Additional hazards when processed	Added	

# 4-Stroke Motorcycle Oil 20W-50 Premium Synthetic

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

7.1	Precautions for safe handling	Added	
7.1	Hygiene measures	Added	
7.1	Handling temperature	Added	
7.2	Technical measures	Added	
7.2	Storage temperature	Modified	
7.2	Storage area	Modified	
8.2	Respiratory protection	Modified	
8.2	Personal protective equipment	Modified	
8.2	Hand protection	Modified	
8.2	Skin and body protection	Modified	
9.1	Solubility	Added	
9.1	Viscosity, kinematic	Modified	
9.1	Odour	Modified	
9.1	Flash point	Modified	
9.1	Colour	Modified	
9.1	Appearance	Modified	
9.1	Density	Modified	
10.1	Reactivity	Modified	
10.2	Chemical stability	Modified	
10.3	Possibility of hazardous reactions	Added	
10.4	Conditions to avoid	Modified	
10.5	Incompatible materials	Modified	
10.6	Hazardous decomposition products	Modified	

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

### SDS MPM REACH

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*