



01000A Motor Oil 15W-50 Multigrade

Document version: May 20, 2024



Description

This mineral motor oil has been specially developed for light duty petrol- and diesel engines of passenger cars. This motor oil is not suitable for turbo engines.

According to the specifications of

API CD / SG

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 01001A | 1 L | 6 | 450 |
| 01020A | 20 L | 1 | 30 |
| 01060A | 60 L | 1 | 6 |
| 01205A | 205 L | 1 | 2 |
| P01000A | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|-------------------------|------------|
| Density at 15°C | 0.886 kg/l | ASTM D4052 |
| Viscosity SAE | 15W-50 | |
| Kinematic Viscosity at 40°C | 170 mm ² /s | ASTM D445 |
| Kinematic Viscosity at 100°C | 18.4 mm ² /s | ASTM D445 |
| Viscosity Index | 121 | ASTM D2270 |
| Dynamic Viscosity at -15°C | 7800 mPa.s | ASTM D5293 |
| Flashpoint COC | 240 °C | ASTM D92 |
| Pourpoint | -33 °C | ASTM D6892 |

These characteristics are typical of current production. Variations in these characteristics may occur.